



## Apollo 350



### Oyster

#### Description

Apollo Series: This cleverly designed fixture with its seamless trim & concealed screws offers this product the diversity of both indoor and or outdoor use. It's IP66 classification allows for insect and weather resistance. The body being made of marine grade die cast aluminium and having a high content of silicone with a UV stabilised hi impact polycarbonate diffuser, not only makes it a great choice for coast locations, but it can be made vandal resistant as well.

#### Specification

Code	LS0100-00-15ND4OX
Mounting	Surface Ceiling or Wall
IP	66
Light Source	LED – CLE G3
Input Voltage	240v 50Hz
Full Systems	16.1w
<u>Luminous Flux</u>	
Opal Diffuser (O)	1116 lm
CCT	4000K (Optional: 3000K)
CRI	>80
Diffuser	Satin opal hi temp polycarbonate polymer, fire retardant, UV stabilised, chemical and oil resistant, non-toxic plastic
Beam Angle	117.9°
Driver	Integral 500mA constant current non-dim (Optional: DALI, DSI dimming.)
Power Factor	>0.9
Product Finish – (X)	Exterior grade polyester powdercoat ( 1 White /2 Silver or 3 Black ) Others colours available upon request)
Dimensions	350mm Ø x 110mm (W)