



Lo-Line Suspended

Extrusion - Direct

Description

Our Lo-Line can be mounted in countless ways, and offers lighting designers nearly infinite possibilities to be creative in ways you never could before and gives you the ability to create a custom Fixture tailored to your specifications

Specification

| | |
|---------------|--|
| Code | LS0600-22-29ND40X |
| Mounting | Suspended |
| IP | 20 (IP44 Available in set lengths) |
| Light Source | LED (Tridonic LLE Advanced Modules) |
| Input voltage | 240v 50hz |
| System Watts | 28.5 |
| Life | 72,000-hour L80F10@65° Celsius |
| Luminous flux | 3087 |
| CCT | 4000K (Optional - 3000K, Tunable white) |
| CRI | 80 (Optional CRI90) |
| Diffuser | Opal (O) |
| Driver | Integral constant current non-dim (Optional – DALI-2, Switch Dim, DALI DT8) |
| Power Factor | 0.93 |
| Includes | 3 metre adjustable ss Y section Suspension Kit |
| Finish (X) | Exterior grade polyester powdercoat (1 White /2 Silver or 3 Black Others colours available upon request) |
| Dimensions | 70mm x 70mm x Nominal 1200mm Continuous lengths available upon request |
| IES File | Yes |

