



## Seal Recessed


### Downlight

#### Description

Seal recessed Downlight LED: This cleverly designed fixture with seamless trim & concealed screws, offers this product the diversity of both indoor and or outdoor use. The body being made of marine grade die cast aluminium and having a high content of silicone with a UV stabilised hi impact polycarbonate diffuser makes it a great choice for coastal locations. Can also be slightly modified to create a vandal resistant product.

#### Specification

Code	LS0200-00-27ND4XX
Mounting	Recessed
IP	66
IK	10
Light Source	LED SLE
Input Voltage	240v 50Hz
Full Systems	26.7 w
Luminous Flux:	Clear 3190 lm
	Frost 3123 lm
CCT	4000k (Optional: 3000K, Tunable white)
CRI	>80 (Optional: CRI90)
Power Factor	>0.9
Diffuser (X)	PC Clear (C) or PC Frosted (F)
Reflector	Aluminium white reflective finish
Driver	Remote constant current non-dim (Optional: DALI, Switch dim, DALI DT8)
Body	Marine grade die-cast aluminium body, locking ring and trim ring
Finish (X)	Exterior grade polyester powdercoat (1 White/ 2 Silver or 3 Black – Other colours upon request)
Dimensions (mm)	290(∅) x 134 (H)
Cut out (mm)	273 ∅



Clear

Frost

